



NCR RealPOS™ 5966 Value Touch

Maximizes

Store
Productivity



- Reliable Touch Display
- Retail Functionality
- Plug and Play Design

Value Touch Designed for Retail

With the ever changing demands of retail, NCR's RealPOS 5966 value touch display is designed and developed to provide a cost-effective touch solution for retailers who want to maximize store productivity and extend the life span of the touch display.

Unlike standard "off the shelf" touch-screen displays, the NCR RealPOS 5966 value touch display includes integrated stereo speakers and an optional three track magnetic stripe reader, two important requirements in retail environments.

By using five-wire resistive touch technology, the screen offers resistance to common retail contaminants, such as dirt grease, water, coffee, vinegar, cleaning detergents and gasoline. Additionally, the NCR RealPOS 5966 performance touch display utilizes VGA for video connections and USB for touch communications.

With quality and reliability in mind, the NCR RealPOS value touch display undergoes environmental and compatibility testing and is manufactured under NCR standards to provide you with confidence that the NCR RealPOS 5966 can deliver POS performance.

Ready to Use Right Out of the Box

Designed to seamlessly integrate within your current point-of-service workstations, the NCR RealPOS 5966 value touch is an all-in-one touch display. The package includes a tabletop mount, as well as the USB touch interface, VGA video connection cables, and US power cord for more user-friendly ordering and installation.

In addition, the NCR RealPOS 5966 supports industry standard OPOS and JavaPOS drivers, standard retail industry applications and operating systems.



NCR RealPOS™ 5966

Value Touch

NCR Service and Support

The NCR RealPOS 5966 Value Touch Display is supported by NCR's global services team offering a wide array of services, including consulting, development, deployment, integration and maintenance. NCR representatives will partner with you to customize a solution for your business and deliver the value that you – and your customers – expect.

For more information, visit www.ncr.com, call 866.431.7879, or e-mail retail.contactus@ncr.com.

Technical Specifications

Display

- Display Size 15"
- Display Type TFT LCD
- Display Resolution XGA
- Resolutions Supported VGA, SVGA, XGA
- Display back-light Dual bulb back light
- Brightness with touch 200 cd2/m

Touch Technology 5-wire Resistive

Connectivity

- Video Interface Analog
- Touch Interface USB
- Power AC line input (or) 12VDC
- Additional Port None

Features and Options

- MSR (USB) 3 track ISO optional
- Speakers Integrated stereo speakers standard
- Remote mount Yes - 75mm VESA compliant
- Integrated Mount For NCR RealPOS 80 and 80c
- Wall Mount Yes

Software Drivers MSR, Touch for Windows and Linux

Physical Specifications

Dimensions (WXDXH)

- without mount 14.0" x 2.5" x 11.75"
- with mount & MSR 15.3" x 7.1" x 14.75"
- Colors Charcoal Gray
- VESA mount compatibility Yes
- Operating range Temperature: 5 to 45° Celsius
Relative humidity: 10-90%

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions, and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR RealPOS is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks, or service marks of their respective holders.

